


FIBER OPTIC CABLE Twintube LSFH

Description

24-.../BQ(ZNG)H-...88

- Metal free indoor and outdoor cable
- Rodent-protected, glass-armoured
- Ripcord for easy jacked removal
- Low smoke, halogen free and self-extinguishing
- Longitudinal and transversal watertight cable



Available Types

Fiber count: 2 up to 24 Fibers

Type of Fiber

E9/125	according to IEC 60793-2-50 Typ B1.3 + ITU G.652.D
E9/125A2	according to IEC 60793-2-50 Typ B6_a2 + ITU G.657.A2
G50/125-OM2	according to IEC 60793-2-10 Typ A1a + ITU G.651
G50/125-OM3	according to IEC 60793-2-10 A1a2 + ITU G.651 BendOptimized
G50/125-OM4	according to IEC 60793-2-10 A1a3 + ITU G.651 BendOptimized
G62.5/125-OM1	according to IEC 60793-2-10 A1b

Standard Colours

Jacket (outer):	Black
-----------------	-------

Technical Data

Construction

Description / Material	Size	Options / Notice
2 Multi-fiber loose tube up to 12 fibers	2.2 mm	Colour, dry
Steel armouring		
2 Ripcords		
Outer jacket / PE flame retardant (LSFH)	8.8 mm	Colour, inscription

Mechanical data

Characteristics	Conditions	Tested acc. to	Values
Weight			92 kg/km
Tensile strength	During installation In service	IEC 60794-1-21 E1	3000 N 1500 N
Minimal bending radius	During installation In service	IEC 60794-1-21 E11	135 mm 90 mm
Crush resistance	During installation In service	IEC 60794-1-21 E3	8000 N/dm 4000 N/dm
Impact resistance	W _p = 1 J	IEC 60794-1-21 E4	100 impacts

FIBER OPTIC CABLE Twintube LSFH

Environmental Data

Characteristics	Conditions	Tested acc. to	Values
Temperature range	During installation In service In storage	IEC 60794-1-22 F1	-10 °C up to +50°C -20 °C up to +70°C -40 °C up to +70°C
Fire load			1.1 MJ/m
Fire propagation	On a vertical single cable	IEC 60332-1-2	passed
Fire Test: smoke density Fire Test: halogen acid gas Fire Test: degree of acidity	Jacket material Jacket material Jacket material	IEC 61034-2 IEC 60754-1 IEC 60754-2	passed halogen free passed
2011/65/EU (RoHS - including 2015/863 and 2017/2102)			compliant
Water penetration	h=1m, 24h, p<3m	IEC 60794-1-2 F5B	passed
(EU) No 305/2011 (CPR)		EN50575	Cca-s1a,d0,a1

Specification for singlemode at 1550nm, for multimode at 1300nm