CABLE GUIDE ROLLER - chain

suitable for universal use - 3-part - roller diameter Ø 130 mm

Item no: 10166





D	Α	T	/	١
_	_	ш	•	•

ITEM NO	10166
DIMENSIONS	L 220.5 x W 155 x H 140 mm
LOAD BEARING CAPACITY	1.500 kg
WEIGHT	9,04 kg
MATERIAL	Roller: Aluminium Frame: Steel
ROLLER DIAMETER	Ø 130 mm
MAX. CABLE DIAMTER	Ø 100 mm
EAN-Code	9120045476385

ADVANTAGES

- Aluminium heavy-duty rollers with stainless steel ball bearings
- Robust metal frame
- **CDP** coating
- **Ergonomic** aluminium carrying handle
- Load capicity 1.500 kg

DESCRIPTION

The cable guide roller - chain is extremely versatile and can be used for pulling cables gently around corners with the least possible resistance. Thanks to its adaptability, it can be used for a wide variety of situations and corners or edges. The cable guide roller - chain can be optionally expanded with additional rollers or links. It can be secured in place with a belt or screws via the assembly opening. The lightweight and highly robust design reduces the effort required with optimum success. The high-quality, die-cast aluminium rollers with integrated ball bearings and the sturdy powder-coated steel frame guarantee a long service life.

Optimum area of application: suitable for universal use, shafts, cable trays, columns, etc.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 psc cable guide roller - chain

INFORMATION

Optional accessories:

POLYESTER PULLING ROPE incl. ree

Rope: Ø 10 mm

Item no: 10167 - 120 m

Item no: 10168 - 200 m

Rope: Ø 12 mm

Item no: 10120 - 150 m

Item no: 10121 - 200 m

Item no: 10122 - 300 m

Item no: 10123 - 350 m



Related pulling system:

Capstan winch CW 800 E

+ trolley

Item no: 10138



