

Features:

- ◆ Expandable braided sleeving to protect cables
- ◆ Flexible cable protection
- ◆ High abrasion resistance
- ◆ Braid construction allows sleeving bore to be expanded up to 300%

Applications

Applications	Where flexibility combined with superior abrasion/cut resistance is required ie mechanical protection of wire harnesses, hoses etc
	For wire bundling that will not trap heat or moisture

Construction

Material	Polyester (PET)
Operating Temp Range	-50°C to 150°C, intermittent +2200°C, melting point +2500°C
Tensile Strength	100,000 PSI
Flammability	UL 224 VW-1-Low Smoke Zero Halogen
Halogen Free	ROHS Compliant



Part Numbers

Item	Description	Width	Length	Colour
776114	Braided Sleeving	10mm-21mm	100Mtr	Black
776116	Braided Sleeving	18mm-32mm	25Mtr	Black
776117	Braided Sleeving	18mm-32mm	25Mtr	Grey
776118	Braided Sleeving	30mm-55mm	25Mtr	Black
776119	Braided Sleeving	30mm-55mm	25Mtr	Grey
776120	Braided Sleeving	57mm-80mm	25Mtr	Black
776121	Braided Sleeving	57mm-80mm	25Mtr	Grey
804532	Braided Sleeving	35mm-64mm	100Mtr	Black
805744	Braided Sleeving	35mm-64mm	100Mtr	Grey
805734	Braided Sleeving	35mm-64mm	25Mtr	Black
805746	Braided Sleeving	35mm-64mm	25Mtr	Grey