

FC-FC OS2 DUPLEX PATCH LEADS

Technical information



Features:

- ◆ Provides moveable links between sections of permanently installed horizontal cable
- ◆ Suitable for use in computer rooms, data centres and work areas
- ◆ Low Smoke Zero Halogen Jacket
- ◆ Tight Buffered Fibre with aramid yarn
- ◆ Full test certificate provided with each lead
- ◆ High quality build and performance
- ◆ Strain relief boots to protect fibre
- ◆ Dust caps provided to keep the fibre face clean
- ◆ Marked transmit and receive legs
- ◆ RoHS compliant construction

Performance & Characteristics

Max Attenuation (dB) 1310nm	0.4
Max Attenuation (dB) 1550nm	0.3
Max Chromatic Dispersion (ps/nm.km) @ 1310nm	3.0
Max Chromatic Dispersion (ps/nm.km) @ 1550nm	18.0
Temperature Range	-40°C to 75°C

Standards

FC Connector Standard	IEC 61754-13
-----------------------	--------------

Physicals

Diameter (mm)	2.0
Housing Colour	Silver



Part Numbers

	Item	Description	Mode	Length	Colour
OS2 9/125µm	782203	Fibre Patch Lead FC-FC	SM	1Mtr	Yellow
	782205	Fibre Patch Lead FC-FC	SM	2Mtr	Yellow
	782206	Fibre Patch Lead FC-FC	SM	3Mtr	Yellow
	782207	Fibre Patch Lead FC-FC	SM	5Mtr	Yellow
	800309	Fibre Patch Lead FC-FC	SM	7Mtr	Yellow
	782204	Fibre Patch Lead FC-FC	SM	10Mtr	Yellow
	798672	Fibre Patch Lead FC-FC	SM	12Mtr	Yellow
	782333	Fibre Patch Lead FC-FC	SM	15Mtr	Yellow
	782334	Fibre Patch Lead FC-FC	SM	20Mtr	Yellow