

# FC-LC OS2 DUPLEX PATCH LEADS

## Technical information



### Features:

- ◆ Provides moveable links between sections of permanently installed horizontal cable
- ◆ Suitable for use in computer rooms, data centres and work areas
- ◆ Low Smoke Zero Halogen Jacket
- ◆ Tight Buffered Fibre with aramid yarn
- ◆ Full test certificate provided with each lead
- ◆ High quality build and performance
- ◆ Strain relief boots to protect fibre
- ◆ Dust caps provided to keep the fibre face clean
- ◆ Marked transmit and receive legs
- ◆ RoHS compliant construction

## Performance & Characteristics

Max Attenuation (dB) 1310nm	0.4
Max Attenuation (dB) 1550nm	0.3
Max Chromatic Dispersion (ps/nm.km) @ 1310nm	3.0
Max Chromatic Dispersion (ps/nm.km) @ 1550nm	18.0
Temperature Range	-40°C to 75°C

## Standards

FC Connector Standard	IEC 61754-13
LC Connector Standard	IEC 61754-20

## Physicals

Diameter (mm)	2.0
Housing Colour	FC - Silver, LC - Blue



## Part Numbers

	Item	Description	Mode	Length	Colour
OS2 9/125µm	782214	Fibre Patch Lead FC-LC	SM	1Mtr	Yellow
	782216	Fibre Patch Lead FC-LC	SM	2Mtr	Yellow
	782217	Fibre Patch Lead FC-LC	SM	3Mtr	Yellow
	782218	Fibre Patch Lead FC-LC	SM	5Mtr	Yellow
	800307	Fibre Patch Lead FC-LC	SM	7Mtr	Yellow
	782215	Fibre Patch Lead FC-LC	SM	10Mtr	Yellow
	800308	Fibre Patch Lead FC-LC	SM	12Mtr	Yellow
	782330	Fibre Patch Lead FC-LC	SM	15Mtr	Yellow
	782331	Fibre Patch Lead FC-LC	SM	20Mtr	Yellow