

LC/PC-LC/APC SINGLEMODE OS2 FIBRE OPTIC SINGLEMODE PATCHLEADS



Technical Information

Ultima patch leads are manufactured to the highest standards and supplied individually bagged with its own test certificate. The transmit and receive leg of each duplex lead is clearly marked to allow for a quick install.

Features:

- ◆ Provides moveable links between sections of permanently installed horizontal cable
- ◆ Suitable for use in computer rooms, data centres and work areas
- ◆ Low Smoke Zero Halogen Jacket
- ◆ Bend Insensitive G657-A2 Fibre
- ◆ 2mm jacket
- ◆ APC Polished Connectors
- ◆ Duplex clips to maintain correct polarity
- ◆ Perfect for high density application
- ◆ Full test certificate provided with each lead
- ◆ High quality build and performance
- ◆ Strain relief boots to protect fibre
- ◆ Dust caps provided to keep the fibre face clean
- ◆ Marked transmit and receive legs

Performance and Characteristics

Max Attenuation (dB) 1310nm	0.4
Max Attenuation (dB) 1550nm	0.3
Max Chromatic Dispersion (ps/nm x km) @ 1310nm	3.0
Max Chromatic Dispersion (ps/nm x km) @ 1550nm	18.0
Temperature Range	-40°C to 75°C

Standards

LC/APC Connector Standard	IEC61754-20
Cable Standard	ITU G.657-A2

Physicals

Sheath Diameter	Ø 2.0mm
Sheath Colour	Yellow
Housing Colour	Green
Boot Colour	White



Part Numbers

	Item Code	Description	Mode	Length
OS2 9/125	802600	Fibre Patch Lead LC/APC-LC/APC	Singlemode	1Mtr
	800899	Fibre Patch Lead LC/APC-LC/APC	Singlemode	2Mtr
	800552	Fibre Patch Lead LC/APC-LC/APC	Singlemode	3Mtr
	800955	Fibre Patch Lead LC/APC-LC/APC	Singlemode	5Mtr
	802601	Fibre Patch Lead LC/APC-LC/APC	Singlemode	10Mtr
	802602	Fibre Patch Lead LC/APC-LC/APC	Singlemode	15Mtr
	801963	Fibre Patch Lead LC/APC-LC/APC	Singlemode	20Mtr
	802603	Fibre Patch Lead LC/APC-LC/APC	Singlemode	25Mtr
	802605	Fibre Patch Lead LC/APC-LC/APC	Singlemode	30Mtr