

Live Fibre Identifier

- ◆ Quickly find fibre in a bundle
- ◆ Indicates signal direction in fibre
- ◆ Indicates live or dark fibre
- ◆ Detects 270Hz, 1kHz, 2kHz tones
- ◆ Suitable for 0.25, 0.9, 2.0, 3.0mm fiber, no need to change adapter



CE

SPECIFICATIONS

Model	OFI1993
Wavelength Range	800 to 1700nm (SM)
Recognizable signal type*	CW, 2kHz, 1kHz, 270Hz $\pm 10\%$
Detector Type	InGaAs 2pcs
Fiber Type	0.9, 0.25, 2.0, 3.0 mm fiber
Sensitivity	+10 ~ -50dBm
Accuracy *	+10dBm to -30dBm (Continuous Wave) / +10dBm to -25 dBm (Modulated Signal)
LED Indicator	Signal direction; signal frequency (2kHz/1kHz/270Hz); low battery
Power Supply	AA x2

STANDARD



Carrying bag



Calibration certificate



Shade Cap



Manual



Packing box

GENERAL SPECIFICATIONS

Size(H*W*D)	230mm * 45mm * 45mm
Weight	About 200g
Storage Temperature	-20 -- +60 °C, < 90%RH
Operating Temperature	-10 -- +50 °C, < 90%RH