

TECHNICAL DATA SHEET

CABLE REFERENCE: D9502A LSZH

PART No.: 53-028-D9502ALSZH

Issue Date: 21/08/2024

Category Type: Belden Alternative

Test Standard: UL1581, UL758

CPR Rating: Eca

SPECIFICATION:

1. Conductor

Material: Stranded Tinned Copper

Inner Conductor (mm): T0.19 × 7 (+/-0.008)

2. Insulation

Material: PVC

Nominal OD (mm): 1.20 (+/- 0.13)

Colour: Black & Red, Black & White

×2 ×2

3. Drain Wire

Material: Stranded Tinned Copper

Nominal OD (mm): T0.19 × 7 (+/- 0.008)

4. Shield

Material: AL-foil

5. Jacket


External OD (mm): 5.65 (+/- 0.20)

Surface: Clean, Smooth

Material: LSZH

Colour: Grey

CABLE CONSTRUCTION



Characteristics

Rated Temperature: 80 °C

Rated Voltage: 300v

Conductor Resistance: < 8.48 Ω/100M

@ 20°C, Conductor DC Resist



Information in this data sheet supplied to users is based on general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of the products, no warranty is given nor is to be implied with respect to such information. Users should make their own enquiries to determine the stability of products for any particular use.